Model Number **261A02**	**3-COMPONENT ICP® FORCE SENSOR**	Revision B ECN #: 33704

Performance	**ENGLISH**	**SI**	
Sensitivity (±20 %) (z axis)	2.5 mV/lb	0.56 mV/N	[1]
Sensitivity (±20 %) (x or y axis)	5 mV/lb	1.12 mV/N	[1]
Measurement Range (z axis)	1000 lb	4.45 kN	
Measurement Range (x or y axis)	1000 lb	4.45 kN	
Maximum Force (z axis)	1320 lb	5.87 kN	
Maximum Force (x or y axis)	1000 lb	4.45 kN	
Maximum Moment (z axis)	40 ft-lb	54.23 Nm	
Maximum Moment (x or y axis)	70 ft-lb	94.91 Nm	
Broadband Resolution (x or y axis)	0.006 lb-rms	0.027 N-rms	[2]
Broadband Resolution (x or y axis)	0.006 lb-rms	0.027 N-rms	[2]
Upper Frequency Limit	10 kHz	10 kHz	
Low Frequency Response (-5 %) (z-axis)	0.01 Hz	0.01 Hz	
Low Frequency Response (-5 %) (x or y axis)	0.001 Hz	0.001 Hz	
Non-Linearity	≤1 % FS	≤1 % FS	[3]
Cross Talk (between x and y axis)	±3 %	±3 %	
Cross Talk (between (x or y axis) and z axis)	±5 %	±5 %	
Environmental			
Temperature Range	-65 to +250 °F	-54 to +121 °C	
Electrical			
Full Scale Output (Z Direction)	±2.5 VDC	±2.5 VDC	
Full Scale Output (X and Y Direction)	±5 VDC	±5 VDC	
Discharge Time Constant (z axis)	≥50 sec	≥50 sec	
Discharge Time Constant (x or y axis)	≥500 sec	≥500 sec	
Excitation Voltage (all channels)	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation (all channels)	2 to 20 mA	2 to 20 mA	
Output Impedance	≤100 Ohm	≤100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Output Polarity	Positive	Positive	
Physical			
Stiffness (z axis)	19 lb/µin	3.3 kN/µm	[2]
Stiffness (x or y axis)	6 lb/µin	1 kN/µm	[2]
Weight	34.40 oz	975 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector	4-Pin	4-Pin	
Electrical Connection Position	Side	Side	

CE[4]

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB group, Inc.

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

M - Metric Mount
W - Water Resistant Cable

Electrical Connection Position	Side	Side

Notes

[1] Sensitivites are for listed preload. Sensitivites may vary ±5% depending on preload used.
[2] Typical.
[3] Zero-based, least-squares, straight line method.
[4] See PCB Declaration of Conformance PS023 for details.

Entered: DMW	Engineer: MJK	Sales: KWW	Approved: ECB	Spec Number:
Date: 08/17/2010	Date: 08/17/2010	Date: 08/17/2010	Date: 08/17/2010	**29368**

PCB PIEZOTRONICS
FORCE / TORQUE DIVISION

3425 Walden Avenue
Depew, NY 14043
UNITED STATES
Phone: 800-828-8840
Fax: 716-684-0987
E-mail: info@pcb.com
Web site: www.pcb.com