

Model Number
260A11

FORCE SENSOR, CHARGE OUTPUT, 3-COMPONENT

Revision N
ECN #: 23150

Performance	ENGLISH	SI	
Sensitivity ($\pm 15\%$) (z axis)	15 pC/lb	3.37 pC/N	[2]
Sensitivity ($\pm 15\%$) (x or y axis)	32 pC/lb	7.19 pC/N	[2]
Measurement Range (z axis)	1000 lb	4.45 kN	
Measurement Range (x or y axis)	500 lb	2.22 kN	
Maximum Force (z axis)	1320 lb	5.87 kN	
Maximum Force (x or y axis)	660 lb	2.94 kN	
Maximum Moment (z axis)	14 ft-lb	18.98 Nm	
Maximum Moment (x or y axis)	13 ft-lb	17.63 Nm	
Upper Frequency Limit	90 kHz	90 kHz	
Non-Linearity	$\leq 1\%$ FS	$\leq 1\%$ FS	[3]
Cross Talk (between x and y axis)	$\pm 3\%$	$\pm 3\%$	
Cross Talk (between (x or y axis) and z axis)	$\pm 5\%$	$\pm 5\%$	
Environmental			
Temperature Range	-100 to +350 °F	-73 to +177 °C	
Electrical			
Capacitance (all channels)	18 pF	18 pF	[1]
Insulation Resistance (all channels)	$\geq 10^{12}$ Ohm	$\geq 10^{12}$ Ohm	
Output Polarity (in direction of markings)	Negative	Negative	
Physical			
Preload	≤ 5000 lb	≤ 22.25 kN	[4]
Stiffness (z axis)	10 lb/ μ in	1.75 kN/ μ m	[1]
Stiffness (x or y axis)	4 lb/ μ in	0.7 kN/ μ m	[1]
Size (Height x Length x Width x Bolt Diameter x ID x Sensing Surface)	0.390 in x 0.950 in x 0.950 in x 0.313 in x 0.319 in x 0.680 in	9.90 mm x 24.1 mm x 24.1 mm x 8 mm x 8.10 mm x 17.27 mm	
Weight	0.868 oz	24.59 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector (Quantity, 3)	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

M - Metric Mount
Supplied Accessory: Model M081A70 Mounting Stud replaces Model 081A70

W - Water Resistant Cable

Electrical Connection Position Side Side

Notes

[1] Typical.

[2] Sensitivities are for listed preload. Sensitivities may vary $\pm 5\%$ depending on preload used.

[3] Zero-based, least-squares, straight line method.

[4] Preload should be at least 10 times the X and Y operating range used.

Supplied Accessories

081A70 Mounting Stud (1)
082B02 Anti-Friction Washer (1)
083A10 Pilot Bushing (1)

Entered: BLS	Engineer: MJK	Sales: JJM	Approved: BLS	Spec Number:
Date: 11/07/2005	Date: 11/09/2005	Date: 11/10/2005	Date: 11/10/2005	6232

All specifications are at room temperature unless otherwise specified.

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB group, Inc.



3425 Walden Avenue
Depew, NY 14043
UNITED STATES
Phone: 800-828-8840
Fax: 716-684-0987
E-mail: info@pcb.com
Web site: www.pcb.com